

C9500 HS Performance

Hi Speed electric WincH

The ultimate winch for Extreme Terrain. Fully Sealed with an unbeatable line Speed of 65 ft/min. Outstanding features includes Huge 6.5 hp high quality double sealed motor with brass fittings, heavy duty waterproof contactors, double sealed drum on maintenance free bearings, quiet, fully sealed efficient full steel planetary gearing. Stainless steel roller fairlead and fittings as standard.





NO LOAD SPEED 65ft/min



Standard Accessories

- 26m x 10.2mm steel cable
- 3m Remote Handset
- Heavy Duty Stainless Steel Fairlead
- Heavy Duty Battery Leads
- Isolation switch
- Stainless Steel Mounting hardware
- Built In Wireless remote
- 5/16 hook

Synthetic Rope and Aluminium fairlead Option

Outstanding Features

- All Brass (no corrosion) Series Wound Motor
- Double Sealed Motor
- Sealed Waterproof Contactor
- Steel Contactor Cover for Added Protection
- Double Sealed Drum (Gearbox/Motor)
- Sealed 3 Stage Planetary Gears
- Stainless Steel 4 Way fairleads
- Integrated Wireless Remote
- Lifetime Mechanical Warranty
- 3 Year Electrical Warranty

Specification	LAYER OF	LINE PULL Ibs/kg	LINE PULL lbs/kg	LINE ft/min	SPEED m/min	AMP 12v	DRAW 24v
RATED LINE PULL: 9500lbs(4500kg)							
MOTOR: 12v: 6.5hp / 4.5kw GEARING: 110:1	1	9500(4309)	0	65	19.8	80	45
BRAKING ACTION: Automatic in the drum DRUM SIZE Dia x L: 63mm x 224mm	2	7706(3495)	4000(1818)	12.5	3.8	300	175
CABLE Dia x L: 9.2mm x 26m MOUNTING PATTERN: 254mm x 114.3mm	3	6482(2940)	6000(2722)	11.81	3.6	400	230
DIMENSIONS: 577mm x 160mm x 215mm	4	5400(2400)	9500(4309)	8.86	1.9	530	335

Limited Lifetime Warranty-includes 3 Year electrical